

# VS



**V880**

**High Volume Cassette & Cartridge  
Conveyer Degausser**

## FEATURES

- High Energy, 5100 Gauss Field
- Fast, Reliable conveyer system
- Erases Cassettes and Cartridges
- Powerful dual "V" configured coils
- Easy to use



## OUR PROMISE

- One Year Warranty, extendable on request
- Lifetime Technical Support
- A trusted brand - Innovators and manufacturers of data destroyer solutions for over 30 years



U.S. 530-626-6924

U.K. +44 (0) 1252 333577

[info@vssecurityproducts.com](mailto:info@vssecurityproducts.com)

[veritysystems.com](http://veritysystems.com)



# INTRODUCTION

The **V880** has been designed to bring efficient erasing of high energy cassettes and cartridges in a conveyer degausser at an affordable price.

The conveyer transportation system of the **V880** ensures that media is completely erased in an easy-to-use manner. Extra security of erasure can be achieved by use of the optional belt cover, ensuring that media cannot be removed from the conveyer belt until it has passed completely through the erasure field.

The cassettes are placed onto the moving conveyer belt and carried over two degaussing coils, which are orientated 90 degrees to one another in a "V" formation. The belt speed is fixed at 4 inches per second (50Hz).



U.S. 530-626-6924

U.K. +44 (0) 1252 333577

[info@vssecurityproducts.com](mailto:info@vssecurityproducts.com)

[veritysystems.com](http://veritysystems.com)



# SPECIFICATIONS

## Media Handling:

### Cassettes and Cartridges:

Beta SP (large and small), Digital Betacam (large and small), D1, D2, D3 (small and medium), MII, Betacam, U-Matic, U-Matic SP, VHS, S-VHS

### Compact Cassettes:

Scotchcart, DAT, 8mm, DLT, 2,3,4,5,6 & SDLT, 3480 & 3490E, TK50,70 & 85, LTO1,2,3,4,5,6,7 & LT08.

**Power Supply:** 220-250V AC 50Hz, 208-220V 60Hz

**Current Rating:** 10 Amps typical

(Please specify Voltage and Frequency when ordering)

**Degaussing Force:** 5100 Gauss

**Erasure Depth:** -75dB on 1500 OE tape (Applies to Audio Tapes only)

**Belt Speed:** 50Hz 4ips, 60Hz 4.8ips

**Belt Width:** 6" (15.24cm)

## Dimensions (WxHxD):

15.6" x 7" x 40.2" (39.6cm x 17.7cm x 102.1cm)

**Unit Weight:** 150lbs (68kg)

**Duty Cycle:** Non-Continuous, 20 Minutes from cold. 60% in the first hour (Dependant on ambient temperature)

**Throughput:** 600 Beta SP Cassettes per hour typical (2 Passes)

**Controls:** On/Off

**Warranty:** 12 Months back to base, all parts & labour included. Extended warranties also available.



U.S. 530-626-6924

U.K. +44 (0) 1252 333577

[info@vssecurityproducts.com](mailto:info@vssecurityproducts.com)

[veritysystems.com](http://veritysystems.com)



# WHO RECOMMENDS HARD DRIVE DEGAUSSING?

As part of their guidelines for sanitization of magnetic media, **degaussing** is recommended by:

- National Institute of Standards & Technology • Department of Defence • Government Security Organizations

The following **Government Mandates** require destruction of sensitive information stored on Hard Drives and Tapes before disposal:

- PCI DSS (Payment Card Industry Data Security Standard) • PIPEDA (Personal Information Protection and Electronic Document Act) • NIST (National Institute of Standards and Technology) • Guidelines for Media Sanitization • NIST SP 800-88 & NIST SP 800-36 • Gramm-Leach-Bliley Act (GLBA) • HIPAA (Health Information Portability and Accountability Act) • California SB-1386 • IRS-1075 • CJIS • Bank Secrecy Act (BSA)
- GDPR (General Data Protection Regulation)

**VS Security Products maintains a policy of continuous improvement and reserves the right to amend this specification without notice.**

U.S. 530-626-6924

[info@vssecurityproducts.com](mailto:info@vssecurityproducts.com)

[veritysystems.com](http://veritysystems.com)



U.K. +44 (0) 1252 333577